

# **beldam lascar seals limited**

**Lascar Works, Hounslow, Middlesex, England TW3 3JL**

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

## **beldam benzoilite jointing**

**beldam benzoilite jointing** is manufactured from specially selected vegetable fibres, impregnated with a mould resisting chemical and processed to give high tensile strength. It is specially treated against deterioration under tropical conditions and does not dry out. It contains no natural rubber or other constituents likely to be affected by petroleum distillates.

**beldam benzoilite jointing** is resilient and for this reason is capable of bedding down to uneven flanges.

### **Fluid Resistance Chart**

<b>1 - Good Resistance</b>	<b>2 - Medium Resistance</b>	<b>3 - Not Resistant</b>			
Acetone	2	Dibutyl Phthalate	1	Lubricating Oil	1
Acids Inorganic	3	Ether	2	Methyl Ethyl Ketone	1
Alcohols(Methyl, Ethyl, Amyl)	1	Ethyl Acetate	1	Nitrobenzene	1
Alkalis	3	Ethylene Glycol	1	Phenol	1
Ammonia	3	Formaldehyde	1	Propane	1
Aniline	1	Freon 12 & 22	3	Propylene Glycol	1
Benzene	1	Fuel Oil	1	Sodium Silicate	1
Butane	1	Gasoline	1	Steam	3
Butyl Acetate	1	Glycerine	1	Toluol	1
Carbolic Acid	1	Greases	1	Trichloroethylene	1
Carbon Dioxide	1	Hydrogen	1	Vegetable Oils	1
Carbon Tetrachloride	1	Hydrogen Peroxide	2	Water (Sea Water)	2
Chlorinated Solvents	1	Hydrogen Sulphide	1	White Spirit	1
Cresol	2	Inks	1	Xylol	1
Detergents	1	Kerosene	1		
		Linseed Oil	1		

**Maximum Temperature 150°C**

**Maximum Pressure 14 bar**

Sheet Size 2 m x 1 m  
Roll Size 1 m wide  
(lengths vary according to thickness)  
Thicknesses from 0.004" to 1/4"  
from 0.1 mm to 6 mm

#### **Storage Instructions**

Never stand rolls, strips or cut joints on concrete floors or concrete shelves, as the jointing may absorb moisture which may lead to deterioration.

Store on wooden pallets or wooden shelves

**Also available in strip or cut joints**