

# **beldam lascar seals limited**

**Lascar Works, Hounslow, Middlesex, England TW3 3JL**

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

[www.beldamlascarseals.co.uk](http://www.beldamlascarseals.co.uk)

## **fibrine jointing compound**

**fibrine jointing compound** is a fibrous compound formulated to withstand extremes of temperature and pressure and beds itself to level up uneven and pitted surfaces.

**fibrine jointing compound** will not attack or corrode metal or plastic and may be used successfully to seal against all common gases and liquids including compressed air, natural gas, fuel oils, transformer oil, sea water, superheated steam, acids and alkaline chemicals.

**fibrine jointing compound**, when mixed with a binding agent such as linseed oil, takes on a pliable plastic form which is ideal for sealing turbine casings, pressure vessels and for joints in high pressure pipelines. The consistency can be varied from thick for flange application to thin for painting on pipe threads.

**fibrine jointing compound**, will remain sufficiently pliable to withstand any movement or vibration of the joint without cracking or disintegrating. When joints have to be broken for maintenance or inspection, the old compound can be quickly and easily removed. A fresh mixture may then be applied and the equipment put back into service immediately.

### **Technical Data**

Form		Powder
Temperature range		-50°C to +600°C
Max. pressure		78 bar
Shelf life	Powder	minimum 1 year (longer if stored in cool place).
	Mixture	2 to 3 days if stored in an air-tight container.

### **Directions for use**

Add boiled linseed oil to the powder and mix thoroughly until the required consistency is obtained.

For flanges                      Mix as hard and stiff as possible so that on being pulled it breaks apart. Apply uniformly to flanges and screw up evenly.

For screw threads              Mix to the consistency of thick paint and apply to threads to cover evenly.

**Supplied in**                      7 kg plastic pail with resealable lid.

**WARNING**      Contains lead monoxide which is harmful by inhalation and if swallowed, danger of cumulative effects. Keep away from food, drink and animal feeding stuffs. When using, do not eat, drink or smoke.