

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

beldam glascar dry packing

beldam glascar dry packing is manufactured from texturised multi-strand continuous filament E glass yarns. These yarns may be plaited into round or square packings.

APPLICATIONS

Sealing furnace doors, boiler casings, metal processing and many high temperature applications where a dry (unlubricated) packing is required.

Maximum Temperature	550°C
pH Range	5 - 11
Flame Resistance	will not burn or smoulder
Chemical Attack	resistant to most chemicals and is unaffected by fungi, bacteria, etc.

beldam glascar dry packing is available in coils in the following lengths.

Other lengths can be made to customers requirements.

<u>section</u> mm	<u>coil size</u> kg	<u>approx. metres per coil</u>	
		<u>round</u>	<u>square</u>
3	1	100	90
3	3	300	270
5	3	145	130
6	3	95	70
8	3	58	48
10	3	38	25
12	3	25	22
15	3	15	13
15	6	30	28
20	6	18	15
25	6	11	10
25	12	22	20
30	12	13	12
40	12	8	6
50	12	4	4