

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

beldam lascarflon XL packing

beldam lascarflon XL packing is manufactured from P.T.F.E. yarns which have been impregnated with P.T.F.E. and silicone oil and is plaited using the lascarlok principal. The result is a self-lubricating packing with excellent properties.

beldam lascarflon XL packing is ideal for high speed pumps both reciprocating and rotary and valves, also food and paper industries in place of asbestos packings.

beldam lascarflon XL packing may be used with Oils, Water, Steam, Solvents, many Acids, Alkalis and most Chemicals, except strong oxidising media, oxygen, oleum or fuming nitric acid.

Max. Temp	Max Pressure	pH range	Max. Shaft Speed
300°C	200 bar	0 - 14	8 m/s

Sizes	Square Section	Length
	3 mm to 25 mm	7.5 m per box

beldam lascarflon XL packing can also be supplied in die-formed rings

Health Warning

Exceeding the recommended maximum temperature may produce fumes which give unpleasant effects when inhaled. Do not use PTFE products with fluorine or molten alkali metals.