

# **beldam lascar seals limited**

**Lascar Works, Hounslow, Middlesex, England TW3 3JL**

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

[www.beldamlascarseals.co.uk](http://www.beldamlascarseals.co.uk)

## **beldam lasgraflon XL packing**

**beldam lasgraflon XL packing** is manufactured from P.T.F.E. yarns which have been impregnated with graphite before plaiting on the lascarlok principal. The result is a self-lubricating packing with outstanding properties.

**beldam lasgraflon XL packing** is ideal for high speed pumps both reciprocating and rotary and valves in place of asbestos packings.

**beldam lasgraflon XL packing** may be used with Oils, Water, Steam, Solvents, many Acids, Alkalis and most Chemicals, except strong oxidising media, oxygen, oleum or fuming nitric acid.

Max. Temp	Max Pressure	pH range	Max. Shaft Speed
<b>300°C</b>	<b>350 bar</b>	<b>0 - 14</b>	<b>25 m/s</b>

Sizes	Square Section	Length
	<b>3 mm to 25 mm</b>	<b>7.5 m per box</b>

**beldam lasgraflon XL packing** can also be supplied in die-formed rings

### **Health Warning**

Exceeding the recommended maximum temperature may produce fumes which give unpleasant effects when inhaled. Do not use PTFE products with fluorine or molten alkali metals.