

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

beldam silascar jointing 9460 & RP9460

beldam silascar jointing 9460 is a solid, red silicone rubber sheeting.

beldam silascar jointing RP9460 is the same as above with one or two ply glass fabric insertion.

beldam silascar jointing RP9460 is used on higher temperature applications than most rubber sheeting.

Hardness	60° Shore 'A' ($\pm 5^\circ$)
Specific Gravity Density	1.28 gr/cm ³
Elongation at Break	300%
Compression Set (22 hours at 177°C)	30%
Tensile Strength	75 kg/cm ²
Tear Strength	17 kg/cm ²

Temperature Range	-60°C to +200°C continuous 250°C intermittent
-------------------	--

Specification	BS:EN:2260:1995 FDA Regulations FDA 21 CFR 177.2600
---------------	--

Supplied 1.2 m wide x 10 m rolls	Thickness 0.8 mm to 10 mm
-------------------------------------	------------------------------

Our range of silicone rubber jointings includes **beldam silascar jointing 9260** (colour white) which is WRC Approved for Hot & Cold Drinking Water.