

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

snoop[®]

Liquid Leak Detector

Snoop[®] liquid leak detector detects gas leaks in hard-to-reach areas.

Features

- Sustained bubble action works even on very small leaks and vertical surfaces.
- Bubble size indicates approximate leak rate.
- Non-toxic, non-corrosive, non-inflammable formula does not contain chlorine, aliphatic amines or ammonium compounds.
- Formula dries clean, without staining.

Technical Information

- Composition: De-ionised water and a surfactant
- Temperature rating: Can be used over a temperature range of -2 to 93°C (27 to 200°F)
- Specifications: Meets the performance requirements of:
 - MIL-PRF-25567 *Leak Detector Compound, Oxygen Systems, Type I, 1 to 70°C (33 to 158°F)*.
 - NFPA 52 Section 3-12.2 *Leak Testing Compressed Natural Gas Vehicular Fuel System*.
 - EPA Part 60, Appendix A, Method 21, Section 4.3.3 *Alternative Screening Procedures Using Soap Solutions*.

WARNING! Use **only** on external surfaces. **Do not** use on internal surfaces.

Available in 236ml (8 fl oz) bottles.