

# beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

## Stag Brand Jointing Pastes A & B

**Stag Brand Jointing Pastes A & B** are easy break, smooth consistency, lead free jointing compounds.

**Stag Brand Jointing Pastes A & B** are ideal for use on all types of flanged or screw threaded joints and have been formulated to meet the most exacting requirements of the automotive, marine, electrical, plumbing and general engineering industries. Both grades are suitable for use on pipework carrying water, brine, steam, gas, fuel oil, diesel oil, petrol or compressed air.

	Stag A	Stag B
Consistency	Thin for general use	Thick for uneven surfaces
Colour	Reddish Brown	Reddish Brown
Solvent Content	22 - 26%	10 - 12%
Flash Point	14°C	14°C
Temperature Range	-40°C to +400°C	-40°C to 650°C
Specific Gravity	1.6	2.13
Available in tin sizes	150 g 400 g 1.5 kg	200 g 500 g 2 kg

### Electrical Properties After 48 hours

Insulation resistance	45,000 megohm/cm
Breakdown voltage	132,000 V/cm

### Resistance Properties

Steam, Water and Brine	Excellent resistance on screwed and flanged joints.
Petrol and Oils	Excellent resistance making it ideal for sealing and lining gearboxes and crankcases.
Gas	Resistant to both natural and town gas.
Acids	Resistant to most dilute mineral acids. Provides good corrosion resistance on battery terminals.

**Application.** Applied by brush to previously cleaned surfaces, free from rust, dirt, oil, grease, etc. In normal circumstances they may be used with or without packing in accordance with normal pipe fitting practice. For very coarse or rough threads or when the joint is liable to extremes of temperature and pressure use type B paste in conjunction with hemp or wick. For very rough flanges use type B with a Taylors Ring.

**Note.** Supplied ready for use but if thickening occurs due to solvent evaporation, they can be returned to their normal consistency by adding Methylated Spirits.

### HEALTH & SAFETY INFORMATION

**Handling Precautions.** Contains industrial Methylated Spirit which, being inflammable, represents the only significant hazard during use. Removal from hands can be effected using a proprietary waterless hand cleaner. Must be shipped on deck if transported by sea.

**Storage.** Store at normal ambient temperature and observe the relevant regulations for the storage of inflammable materials. Shelf life is at least one year in unopened containers.