

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

beldam lascarflon GT thread seal



beldam lascarflon GT thread seal is manufactured from Polytetrafluoroethylene (P.T.F.E.), which is an inert non-toxic thermoplastic Gas Tape with a very low coefficient of friction. This latter property ensures that joints can easily be broken after very considerable periods of time.

beldam lascarflon GT thread seal is resistant to the most aggressive organic and inorganic chemicals and solvents. It can also be used with potable water, acids, alkalis, alcohol, oils, steam and all common liquids and gases including oxygen without contamination.

beldam lascarflon GT thread seal is also resistant to enzymatic and micro biological attack and does not contain any additives that could provide a substrate for fungal or bacterial growth.

beldam lascarflon GT thread seal is a high density thread tape which is more than twice the thickness of standard thread tape and you use only one wrap with a 50% overlap.

Maximum Temperature

260°C

Specifications

EN751.3GRp

BS7786:1995:Grade M

(supersedes BS5292/BS6974:1989)

DIN-DVGW 30660 (UK Water Council)

EN Norm 751/3

GasTec NL

U.S. mil-spec. T27730A

Supplied

12 mm x 5 m x 0.2 mm

19 mm x 15 m x 0.2 mm