

beldam lascar seals limited

Lascar Works, Hounslow, Middlesex, England TW3 3JL

Tel 020 8570 7722 Intl Tel +4420 8570 7722

Fax 020 8570 4438 Intl Fax +4420 8570 4438

www.beldamlascarseals.co.uk

beldam zig-zag AG packing

beldam zig-zag AG packing is built up of alternate layers of anti-friction white metal and fine woven glass cloth moulded at an angle of 45° to the rod. The slightest pressure is sufficient to expand the packing laterally and its cross-expansion construction also makes it suitable for use with rods that are worn or subject to vibration.



beldam zig-zag AG packing has great expansion under steam and it is recommended that after the gland has been brought home it is slackened back until the nuts are finger-tight. Care should be taken to ensure that the gland has sufficient entry to permit slackening off.

beldam zig-zag AG packing is particularly recommended for rods and spindles on marine and stationary engines and auxiliary steam plants, i.e. pumps, expansion glands, bilge water, compressors, winches and hoists.

Max. Temp.
290°C

Max. Pressure
50 bar

pH Range
6 - 11

Max. Shaft Speed
2 m/s

Square Sections

3 mm to 10 mm
11 mm to 25 mm
above 25 mm

15 m per box
7.5 m per box
3.75 m per box

beldam zig-zag AG packing also in sets of moulded split rings in all sizes.